

Amendments to the Claims:

This listing of claims will replace all prior versions and listing of claims in the application.

Listing of Claims:

1. (Original) A spark ignition engine, comprising:

combustion control means for controlling ignition timing by an ignition plug;

and

turbulence generating means for generating turbulence in an exhaust flow in an exhaust passage, wherein:

the combustion control means makes ignition timing immediately before a compression stroke top dead center or later in the case where the temperature of the engine is lower than the predetermined temperature.

2. (Original) A spark ignition engine according to Claim 1, comprising:

fuel stratifying means for stratifying fuel in a combustion chamber, wherein:

the combustion control means instructs the fuel stratifying means to layer fuel in the combustion chamber in the case where the temperature of the engine is lower than the predetermined temperature.

3. (Original) A spark ignition engine according to Claim 1, comprising:

a fuel injection valve for directly injecting fuel into the combustion chamber, wherein:

the combustion control means instructs the fuel injection valve to inject fuel at a compression stroke in the case where the temperature of the engine is lower than the predetermined temperature.

4. (Original) A spark ignition engine, comprising:

turbulence generating means for generating turbulence in an exhaust flow in an exhaust passage;

a fuel injection valve for directly injecting fuel into a combustion chamber; and

fuel injection control means for controlling fuel injection timing by the fuel injection valve, wherein:

the fuel injection control means instructs the fuel injection valve to inject fuel at an expansion stroke in the case where the temperature of the engine is lower than the predetermined temperature.

5. (Original) A spark ignition engine, comprising:

ignition timing control means for controlling ignition timing by an ignition plug;

a fuel injection valve for directly injecting fuel into a combustion chamber; and

fuel injection control means for controlling fuel injection timing by the fuel injection valve, wherein:

the penetration of fuel spray injected from the fuel injection valve in the direction of an ignition plug is made longer than that in the direction of a piston;

in the case where the temperature of the engine is lower than the predetermined temperature, the fuel injection control means instructs the fuel injection valve to inject fuel in the second half of a compression stroke so that the air-fuel ratio is in the vicinity of the theoretical air-fuel ratio; and

the ignition timing control means makes ignition timing immediately before a compression stroke top dead center or later.

6. (Original) A spark ignition engine, comprising:

ignition timing control means for controlling ignition timing by an ignition plug;
a fuel injection valve for directly injecting fuel into a combustion chamber;
fuel injection control means for controlling fuel injection timing by the fuel injection valve; and

longitudinal vortex generating means for generating a forward longitudinal vortex in a combustion chamber, wherein:

in the case where the temperature of the engine is lower than the predetermined temperature, the longitudinal vortex generating means generates a forward longitudinal vortex in the combustion chamber;

the fuel injection control means instructs the fuel injection valve to inject fuel in the second half of a compression stroke so that the air-fuel ratio is in the vicinity of the theoretical air-fuel ratio; and

the ignition timing control means makes ignition timing immediately before a compression stroke top dead center or later.

7. (Original) A spark ignition engine, comprising:

ignition timing control means for controlling ignition timing by an ignition plug;
a fuel injection valve for directly injecting fuel into a combustion chamber;
fuel injection control means for controlling fuel injection timing by the fuel injection valve; and

longitudinal vortex generating means for generating a forward longitudinal vortex in the combustion chamber, wherein:

the penetration of fuel spray injected from the fuel injection valve in the direction of an ignition plug is made longer than that in the direction of a piston;

in the case where the temperature of the engine is lower than the predetermined temperature, the longitudinal vortex generating means generates a forward longitudinal vortex in the combustion chamber;

the fuel injection control means instructs the fuel injection valve to inject fuel in the second half of a compression stroke so that the air-fuel ratio is in the vicinity of the theoretical air-fuel ratio; and

the ignition timing control means makes ignition timing immediately before a compression stroke top dead center or later.

8. (Original) A spark ignition engine according to Claim 6, comprising:

longitudinal vortex controlling means for controlling the strength of a forward longitudinal vortex generated in the combustion chamber; and

fluctuation detecting means for detecting the magnitude of the fluctuation of engine speed or torque fluctuation, wherein:

the longitudinal vortex controlling means controls the strength of the longitudinal vortex so that the magnitude of the fluctuation of engine speed or torque fluctuation is a predetermined value or less; and

the ignition timing control means delays ignition timing to the extent possible.

9. (Original) A spark ignition engine according to Claim 7, comprising:

longitudinal vortex controlling means for controlling the strength of a forward longitudinal vortex generated in the combustion chamber; and

fluctuation detecting means for detecting the magnitude of the fluctuation of engine speed or torque fluctuation, wherein:

the longitudinal vortex controlling means controls the strength of the longitudinal vortex so that the magnitude of the fluctuation of engine speed or torque fluctuation is a predetermined value or less; and

the ignition timing control means delays ignition timing to the extent possible.

10. (Original) A spark ignition engine, comprising:

ignition timing control means for controlling ignition timing by an ignition plug;

a fuel injection valve for directly injecting fuel into a combustion chamber;

fuel injection control means for controlling fuel injection timing by the fuel injection valve;

fuel pressure controlling means for controlling the pressure of fuel supplied to the fuel injection valve; and

fluctuation detecting means for detecting the magnitude of the fluctuation of engine speed or torque fluctuation, wherein:

in the case where the temperature of the engine is lower than the predetermined temperature, the fuel injection control means instructs the fuel injection valve to inject fuel in the second half of a compression stroke so that the air-fuel ratio is in the vicinity of the theoretical air-fuel ratio;

the fuel pressure controlling means controls fuel pressure so that the magnitude of the fluctuation of engine speed or torque fluctuation is a predetermined value or less; and

the ignition timing control means delays ignition timing to the extent possible.

11. (Original) A spark ignition engine according to Claim 3, wherein:

time interval between the latest fuel injection initiation timing and ignition initiation timing is 9 ms or longer.

12. (Original) A spark ignition engine according to Claim 5, comprising:
turbulence generating means for generating turbulence in an exhaust flow in the exhaust passage.
13. (Original) A spark ignition engine according to Claim 1, comprising:
a fuel injection valve for injecting fuel into an intake port, wherein:
said combustion control means instructs the fuel injection valve to inject fuel at an intake stroke in the case where the temperature of the engine is lower than the predetermined temperature.
14. (Original) A spark ignition engine according to Claim 1, wherein:
said turbulence generating means is mounted in an exhaust passage at the position where the exhaust temperature in warming-up operation is 600°C or higher.
15. (Original) A spark ignition engine according to Claim 1, wherein:
said turbulence generating means is mounted in an exhaust passage at the position which is within 500 mm downstream from the most upstream part of the exhaust passage.
16. (Original) A spark ignition engine according to Claim 1, wherein:

the cross-sectional area of an exhaust passage in the vicinity of said turbulence generating means mounted therein, is made larger than at least the cross-sectional area of upstream part of the passage.

17. (Original) A spark ignition engine according to Claim 1, wherein:

said turbulence generating means is configured by plural rods or plural plates arranged in parallel so that they cross the exhaust passage.

18. (Original) A spark ignition engine according to Claim 1, wherein:

said turbulence generating means is configured in the form of a grid or a cobweb.

19. (Original) A spark ignition engine according to Claim 17, wherein:

the interval between component members of said turbulence generating means is narrower on the wall side, as compared with that in the center of the exhaust passage.

20. (Original) A spark ignition engine according to Claim 1, wherein:

said turbulence generating means is configured by plural projections or annular members protruded inwardly from an inner wall of the exhaust passage.

21. (Original) A spark ignition engine according to Claim 1, wherein:

said turbulence generating means is configured by a step mounted on an inner wall of the exhaust passage.

22. (Original) A spark ignition engine according to Claim 17, wherein:

said turbulence generating means is integrated with a gasket arranged between the exhaust passage and a cylinder head.

23. (Original) A spark ignition engine according to Claim 17, wherein:

said turbulence generating means is held between or positioned adjacently to gaskets arranged between the exhaust passage and a cylinder head.

24. (Original) A spark ignition engine according to Claim 17, wherein:

said turbulence generating means can be electrically heated.

25. (Original) A spark ignition engine according to Claim 17, wherein:

said turbulence generating means is arranged so that the width of the component member is $Rec \cdot v/U_e$ or more, where Rec is the critical Reynolds number at which a Karman vortex is generated, U_e is the mean exhaust velocity in the exhaust passage in warming-up operation and v is the kinematic coefficient of viscosity of exhaust gas.

26. (Currently Amended) A combustion control method of a spark ignition engine,
~~which comprising the steps of:~~

generating turbulence in an exhaust flow in an exhaust passage, and
~~causing~~ makes ignition timing to occur immediately before a compression
stroke top dead center or later in the case where ~~at~~ the temperature of the engine is
lower than ~~at~~ the predetermined temperature,.

27. (Currently Amended) A combustion control method according to Claim 26,
further comprising the step of instructing to stratify fuel in the combustion chamber
which in the case where the temperature of the engine is lower than the
predetermined temperature, ~~makes fuel stratified in a combustion chamber.~~

28. (Currently Amended) A combustion control method according to Claim 26,
further comprising the step of injecting fuel in a compression stroke ~~which in the case~~
where the temperature of the engine is lower than the predetermined temperature,
~~injects fuel in a compression stroke.~~

29. (Currently Amended) A combustion control method of a spark ignition engine,
comprising the steps of:

~~which~~ generating turbulence in an exhaust flow in an exhaust passage; and

injectings fuel directly into a combustion chamber; and
injecting fuel in an expansion stroke in the case where athe temperature of the engine is lower than athe predetermined temperature, ~~inject fuel in an expansion stroke.~~

30. (Currently Amended) A combustion control method of a spark ignition engine, comprising the steps of:

~~which makes~~causing penetration of injected fuel spray in athe direction of an ignition plug longer than that in athe direction of a piston; ~~and~~

in the case where athe temperature of the engine is lower than athe predetermined temperature, injectings fuel in athe second half of a compression stroke so that anthe air-fuel ratio is in athe vicinity of athe theoretical air-fuel ratio; and

causing ~~makes~~ ignition timing to occur immediately before a compression stroke top dead center or later.

31. (Currently Amended) A combustion control method of a spark ignition engine, ~~which~~comprising the steps of:

in the case where athe temperature of the engine is lower than athe predetermined temperature, generatinges a forward longitudinal vortex in a combustion chamber;

injectings fuel in athe second half of a compression stroke so that anthe air-fuel ratio is in athe vicinity of athe theoretical air-fuel ratio; and
causingmakes ignition timing to occur immediately before a compression stroke top dead center or later.

32. (Currently Amended) A combustion control method of a spark ignition engine, which comprising the steps of:

causingmakes penetration of injected fuel spray in athe direction of an ignition plug longer than that in the direction of a piston;

in the case where athe temperature of the engine is lower than athe predetermined temperature, generatinges a forward longitudinal vortex in a combustion chamber;

injectings fuel in athe second half of a compression stroke so that anthe air-fuel ratio is in athe vicinity of athe theoretical air-fuel ratio; and

causingmakes ignition timing to occur immediately before or later than a compression stroke top dead center.

33. (Currently Amended) A combustion control method according to Claim 31, comprising the steps of~~which~~:

regulating~~ing~~ the strength of a forward longitudinal vortex generated in ~~at~~the combustion chamber so that ~~at~~the magnitude of ~~at~~the fluctuation of engine speed or torque fluctuation is a predetermined value or less; and
delaying~~ing~~ ignition timing to ~~an~~the extent possible.

34. (Currently Amended) A combustion control method of a spark ignition engine, comprising the steps of~~which~~:

in the case where ~~at~~the temperature of the engine is lower than ~~at~~the predetermined temperature, injecting~~ing~~ fuel in ~~at~~the second half of a compression stroke so that ~~an~~the air-fuel ratio is in ~~at~~the vicinity of ~~at~~the theoretical air-fuel ratio;

regulating~~ing~~ ~~an~~the injection pressure of fuel so that ~~at~~the magnitude of ~~at~~the fluctuation of engine speed or torque fluctuation is a predetermined value or less;
and

delaying~~ing~~ ignition timing to ~~an~~the extent possible.

35. (Currently Amended) A combustion control method according to Claim 28, further comprising the step of~~which~~:

setting~~ing~~ a time interval between ~~a~~the latest fuel injection initiation timing and ~~an~~the ignition initiation timing to 9 ms or more.

36. (Currently Amended) A combustion control method according to Claim 26,
further comprising the steps of which:

injectings fuel into an intake port; and

in the case where the temperature of the engine is lower than the
predetermined temperature, injectings fuel in an intake stroke.